


# CZ087



2 Coaxial way  
Treated cellulose fiber diaphragm  
Neodymium tweeter


## GENERAL SPECIFICATIONS

Program power	80 W
Rated impedance	4 Ω
Nominal diameter	3" - 87 mm
Sensitivity (1W/1m)	86 dB
Voice coil diameter	25 mm
Frequency range	-

## TECHNICAL SPECIFICATIONS

Power handling capacity	30 W
Gap height	3 mm
N. of mounting holes	1 ø 4 / ø 112
Front mount baffle cutout ø	77 mm
Re	3,50 Ω
Fs	177 Hz
Qms	5,56
Qes	2,57
Qts	1,76
Mms	2,00 g
Cms	0,41 mm/N
D	65 mm
Vas	0,62 dm³
B · l	1,74 Wb/m
Xmax	1,60 mm
η <sub>o</sub>	-
Le	-
Net weight	0,35 Kg
Recommended loading	-
Volume / Tuning frequency	-

# CZ100



2 Coaxial way  
Treated cellulose fiber diaphragm  
Neodymium tweeter  
Removable fixing side basket

## GENERAL SPECIFICATIONS

Program power	80 W
Rated impedance	4 Ω
Nominal diameter	4" - 100 mm
Sensitivity (1W/1m)	91 dB
Voice coil diameter	25 mm
Frequency range	-

## TECHNICAL SPECIFICATIONS

Power handling capacity	30 W
Gap height	4 mm
N. of mounting holes	4 ø 5,5 / ø 116
Front mount baffle cutout ø	91 mm
Re	3,50 Ω
Fs	160 Hz
Qms	4,89
Qes	1,34
Qts	1,05
Mms	2,83 g
Cms	0,35 mm/N
D	80 mm
Vas	1,23 dm³
B · l	2,73 Wb/m
Xmax	1,10 mm
η <sub>o</sub>	-
Le	-
Net weight	0,47 Kg
Recommended loading	-
Volume / Tuning frequency	-