


# CZ131



2 Coaxial way  
Treated cellulose fiber diaphragm  
Neodymium tweeter


## GENERAL SPECIFICATIONS

Program power	100 W
Rated impedance	4 Ω
Nominal diameter	5"- 130 mm
Sensitivity (1W/1m)	91 dB
Voice coil diameter	25 mm
Frequency range	-

## TECHNICAL SPECIFICATIONS

Power handling capacity	50 W
Gap height	4 mm
N. of mounting holes	4 ø 5 / ø 140
Front mount baffle cutout ø	112 mm
Re	3,50 Ω
Fs	119 Hz
Qms	6,05
Qes	1,85
Qts	1,41
Mms	5,70 g
Cms	0,35 mm/N
D	106 mm
Vas	3,85 dm³
B · l	2,68 Wb/m
Xmax	1,10 mm
η <sub>o</sub>	-
Le	-
Net weight	0,51 Kg
Recommended loading	-
Volume / Tuning frequency	-

# CZ170



2 Coaxial way  
Treated cellulose fiber diaphragm  
Neodymium tweeter

## GENERAL SPECIFICATIONS

Program power	100 W
Rated impedance	4 Ω
Nominal diameter	6,5"- 165 mm
Sensitivity (1W/1m)	91 dB
Voice coil diameter	25 mm
Frequency range	-

## TECHNICAL SPECIFICATIONS

Power handling capacity	50 W
Gap height	4 mm
N. of mounting holes	4 ø 5 / ø 157
Front mount baffle cutout ø	142 mm
Re	3,50 Ω
Fs	104 Hz
Qms	4,59
Qes	2,16
Qts	1,47
Mms	7,05 g
Cms	0,33 mm/N
D	130 mm
Vas	8,16 dm³
B · l	2,73 Wb/m
Xmax	1,10 mm
η <sub>o</sub>	-
Le	-
Net weight	0,71 Kg
Recommended loading	-
Volume / Tuning frequency	-